



**MARIE**

APPLIED SCIENCE IN THE SERVICE OF  
RETHINKING AND IMPROVING  
ENERGY EFFICIENCY

**AREA**

SciencePark

Dipartimento di Ingegneria e Architettura  
Università degli Studi di Trieste

Via Valerio, 10

Tel: +390405583051

Fax: +390405583812

Email: [salessandrini@units.it](mailto:salessandrini@units.it), [taccani@units.it](mailto:taccani@units.it), [micheli@units.it](mailto:micheli@units.it)

PA3.2 Task 5: Test under real conditions of innovative products for the building sector

# Performance analysis and experimental data collection on photovoltaic arrays installed on building Q2 and building CTB in the AREA Science Park campus of Basovizza

## EXECUTIVE SUMMARY

Author: Stefano Alessandrini

Scientific supervisor: Rodolfo Taccani

ver. 0.1	Experimental data and software description	SA	RT, DM
<b>Release</b>	<b>Description</b>	<b>Authors</b>	<b>Review</b>

## **1. INTRODUCTION**

One of the activities carried out by the Engineering and Architecture Department of the University of Trieste for the MARIE project has been to monitor the performance of photovoltaic arrays (PV) installed on the roofs of three buildings in the Area Science Park campus of Basovizza (Trieste - Italy). The aim of this report is to verify the performance of PV systems with crystalline silicon modules installed on the roofs of the buildings Q2 and CTB (Centrale Tecnologica Basovizza) whose monitoring is active since October 2011 and the presentation of some results obtained through an energy analysis software tool developed in order to assess on field technical - economic performance of different photovoltaic arrays.

## **2. PILOT ACTION DESCRIPTION**

The action involves the evaluation of the performance of photovoltaic modules with which are equipped the considered arrays. It has been possible to check in particular the efficiency of the modules under real operating conditions and estimate the extent of performance degradation over time. Furthermore, the action gives the possibility to access the experimental data to the sector workers, and the SW, which is calibrated on this experimental data, could give the possibility of evaluate the integration of this kind of systems also to the manufacturer of other technologies.

### **2.1 OBJECTIVES**

The activity is driven by motivations that are both technical and economic, which are:

- the assessment of the performance of the system and its components;
- the assessment of the system efficiency through the correlation between the actual measurement of the solar radiation and the energy produced;
- the assessment of the degradation of components and performance;
- the assessment of the real efficiency under real conditions;
- the identification of the most suitable and more cost effective solution for the production of electricity by small plants (software ENPAT).

## 2.2 PILOT ACTION'S INDUSTRIAL FALLOUT

The pilot action is intended to serve the realization of a tool/database focused on performance and reliability of energy systems which enable researchers, manufacturers, installers, policy-makers and the public to obtain useful comparative information, from a large and significant number of distributed systems of primary energy production. The laboratory will provide a technical and scientific platform capable of activating public and private partnerships and business ventures in terms of energy efficiency and use of renewable resources. The pilot action, supported by the key actors involved, will be able to promote the marketing of new products and services to support a more efficient and rational use of energy.

## 2.3 ENVIRONMENTAL IMPACT

From the social point of view photovoltaic systems reduce the demand for energy from other traditional sources contributing to the reduction of air pollution. Nevertheless, we must remember that the massive use of the energy produced by the photovoltaic involves very serious problems in the management of electricity distribution networks and existing power plants. So a massive and irrational use of photovoltaic energy may lead to a real increase in emissions of carbon dioxide rather than to reduce them.

## 3. MAIN RESULTS

The analysis carried out on the considered photovoltaic arrays has allowed:

- to assess the influence of the temperature of the modules on the performance;
- to compare the on field average efficiency of the module with the manufacturer specifications. For the CTB photovoltaic array in the standard working conditions the measured efficiency was 15.7% and the manufacturer specification is 16.6%. For the Q2 photovoltaic array in the standard working conditions the measured efficiency was 16.45% and the manufacturer specification is 18.4%;
- to implement the experimental data in the energy performance software tool ENPAT.

## 4. CONCLUSIONS AND TECHNICAL-ECONOMIC FEASIBILITY

The efficiency of the panels is close to that of the specification and over a period of 12 months performance has not changed. Nowadays, as the installation of PV is given small or no economic incentives, there is the need to identify with accuracy the investment pay-back period. The energy performance analysis software tool developed, allows to assess the pay-back period in different

scenarios and system configurations. Therefore, the outcome of the study can be used to determine future economic incentive schemes.